

RBS-2

SIDE SHIFT ROTARY TILLER



The side shift RBS-2 tiller has been designed in a way to enhance the efficiency and toughness of the machine without compromising on the versatility and simplicity of its use. The unique 3 point hitch system allows for easy and secure offset of the machine.

Italian Passion & Technology
Made in Modena



SOVEMA S.r.l.
Via Olmo, 6
41013 Gaggio di Piano (MO) ITALY
Ph. +39 059 93 85 85
Fx. +39 059 93 85 12
E-mail: sovema@sovema.com
Web-site: www.sovema.com

SOVEMA-AGRITAL Cab Factory
Via Leonardo da Vinci, 20
24040 Arzago d'Adda (BG) ITALY
Ph. +39 0363 87 633
Fx. +39 0363 87 355
E-mail: sovema@agritalsovema.com
Web-site: www.agritalsovema.com












SOVEMA Inc.
1836 Vanderhorn Drive
Memphis, TN 38134 U.S.A.
Ph. 901 388 8869
Fx. 901 388 8348
E-mail: sovema@sovemausa.com
Web-site: www.sovemausa.com

SOVEMA CANADA Ltd.
4845 Portage Avenue
Headingley, MB R4H 1C7 CANADA
Ph. 204 927 9042
Fx. 204 897 6975
E-mail: sovema@sovemacanada.com
Web-site: www.sovemacanada.com

STANDARD FEATURES FOR RBS-2

RBS-2 side shift rotary tillers serie is suitable to be used in difficult low clearance conditions such as orchards, vineyards and greenhouses.

- For tractors up to 45 HP
- I and II Category linkage
- Automatic linkage
- Rotor with 4 blades per flange
- Speed or square blades
- Adjustable skids with side guards
- ASA 100 drive chain
- Safety guards
- PTO at 540 rpm
- Single-speed gearbox
- Telescopic guard
- Manual side shift
- In house Sovema gearbox production

Side shift details		
	(cm-inches)	(cm-inches)
RBS-2 100	48 - 19" 	52 - 20" 
	12 - 5" 	88 - 35" 
RBS-2 110	48 - 19" 	62 - 24" 
	12 - 5" 	98 - 39" 
RBS-2 120	58 - 23" 	62 - 24" 
	12 - 5" 	108 - 43" 
RBS-2 130	58 - 23" 	72 - 28" 
	12 - 5" 	118 - 46" 
RBS-2 140	63 - 25" 	77 - 30" 
	12 - 5" 	128 - 50" 
RBS-2 150	48 - 27" 	82 - 32" 
	12 - 5" 	138 - 54" 

Model	Working Width	Weight	HP	PTO	Rotor	Blades
	(cm-inches)	(Kg-Lbs)		(rpm)	(rpm)	
RBS-2 100	100 - 40"	200 - 440	20 - 30	540	208	20
RBS-2 110	110 - 44"	208 - 458	20 - 30	540	208	24
RBS-2 120	120 - 48"	216 - 476	25 - 35	540	208	24
RBS-2 130	130 - 52"	228 - 502	25 - 35	540	208	28
RBS-2 140	140 - 56"	239 - 526	30 - 35	540	208	28
RBS-2 150	150 - 60"	252 - 555	30 - 45	540	208	32

Technical data are subject to change and not binding



Distributed by:

Your local Dealer: